RULES FOR FLOATING DOCKS

Rules for Floating Docks

2010 AMENDMENT NO.1

Rule No.92 15th October 2010

Resolved by Technical Committee on 6th July 2010

Approved by Board of Directors on 27th July 2010



Rule No.92 15th October 2010 AMENDMENT TO THE RULES FOR FLOATING DOCKS

"Rules for floating docks" has been partly amended as follows:

Chapter 2 CLASSIFICATION SURVEYS

2.1 Classification Surveys during Construction

2.1.1 General

Sub-paragraph -2 has been amended as follows.

- 2 In principle, newThe new installation of materials which contain asbestos is to be prohibited. Where deemed as necessary by the Society, the installation may be allowed in such positions as shown below:
- (1) vanes used in rotary vane compressors and rotary vane vacuum pumps;
- (2) watertight joints and linings used for the circulation of fluid when, at high temperature in excess of 350°C or pressure in excess of 7 MPa, there is a risk of fire, corrosion or toxicity; and
- (3) supple and flexible thermal insulation assemblies used for temperatures above 1,000°C.

2.1.2 Plans and Documents

Sub-paragraph (2)(h) has been deleted.

When a dock is intended to be classed with the Society, plans and documents showing the scantlings, arrangements and details of the principal parts of the structure, and relevant data are to be submitted for review or approval. Plans for approval are generally to be submitted in triplicate. In general, these plans and documents are to include the following (1) and (2) where applicable.

- (2) Information
 - (h) Where materials which contain asbestos are used, documents including the location and other detailed information.

2.4 Preparation for Surveys and Others

2.4.1 Preparation for Surveys and Others

Sub-paragraph -6 has been added as follows.

6 Replacement of fittings, equipments and parts, etc.

In where it is necessary to replace any fittings, equipment or parts, etc. used onboard, replacements are to be comply with the regulations to be applied during ship construction. However, in cases where new requirements are specified or where deemed necessary by the Society, the Society may require that such replacements comply with any new requirements in effect at the time the relevant replacement work is carried out. In addition, replacements are not to use any materials which contain asbestos

EFFECTIVE DATE AND APPLICATION

1. The effective date of the amendments is 1 January 2011.