# **Machinery of Polar Class Ships**

# **Object of Amendment**

Rules for the Survey and Construction of Steel Ships Part I

#### **Reason for Amendment**

IACS Unified Requirements (UR) I3(Rev.2) specifies requirements for the machinery of Polar Class Ships, and these requirements have already been incorporated into the NK Rules.

IACS adopted UR I3(Rev.2, Corr.1) in December 2024 to correct some descriptive errors found in formulae and other things in UR I3(Rev.2).

Accordingly, relevant requirements are amended based on the UR I3 (Rev.2, Corr.1).

## **Outline of Amendment**

Amends formula for determining the number of ice load cycles per propeller blade.

## **Effective Date and Application**

Effective date of this amendment is 1 January 2026.

ID:DD25-16

Amended-Original Requirements Comparison Table (Machinery of Polar Class Ships)

Amended-Original Requirements Comparison Table (Machinery of Polar Class Ships)			
Amended	Original	Remarks	
RULES FOR THE SURVEY AND	RULES FOR THE SURVEY AND		
CONSTRUCTION OF STEEL SHIPS	CONSTRUCTION OF STEEL SHIPS		
Part I SHIPS OPERATING IN POLAR	Part I SHIPS OPERATING IN POLAR		
WATERS, POLAR CLASS SHIPS	WATERS, POLAR CLASS SHIPS		
AND ICE CLASS SHIPS	AND ICE CLASS SHIPS		
ANNEX 1 SPECIAL REQUIREMENTS FOR	ANNEX 1 SPECIAL REQUIREMENTS FOR		
THE MATERIALS, HULL STRUCTURES,	THE MATERIALS, HULL STRUCTURES,		
EQUIPMENT AND MACHINERY OF POLAR	EQUIPMENT AND MACHINERY OF POLAR		
CLASS SHIPS	CLASS SHIPS		
Chapter 4 MACHINERY INSTALLATIONS	Chapter 4 MACHINERY INSTALLATIONS		
•			
11 7 1			
4.4 Design Loads	4.4 Design Loads		
4.4.8 Number of Ice Loads	4.4.8 Number of Ice Loads		
1 The number of load cycles per propeller blade in the	1 The number of load cycles per propeller blade in the	UR I3(Corr.1) Para.5.3.9	
load spectrum is to be determined according to the following	load spectrum is to be determined according to the following		
formula:	formula:	Carra farmania as Chantan	
$N_{ice} = k_1 k_2 k_3 N_{class} \frac{n_n}{60}$	$N_{ice} = k_1 k_2 N_{class} \frac{n_n}{60}$	Same formula as Chapter 8, 8.5.5-2, Part I of the	
where	where	Rules	
$N_{class}$ : Reference number of loads for ice classes,	$N_{class}$ : Reference number of loads for ice classes,		
as specified in Table 4.4.8-1	as specified in Table 4.4.8-1		
n <sub>n</sub> : Nominal propeller rotational speed at	$n_n$ : Nominal propeller rotational speed at		
maximum continuous revolutions in free	maximum continuous revolutions in free		

Amended-Original Requirements Comparison Table (Machinery of Polar Class Ships)

	Comparison Table (Machinery of Polar Class Snips)	
Amended	Original	Remarks
running condition (rpm)	running condition (rpm)	
<i>k</i> <sub>1</sub> : Propeller location factor, as specified in <b>Table</b>	$k_I$ : Propeller location factor, as specified in <b>Table</b>	
4.4.8-2	4.4.8-2	
$k_2$ : The submersion factor $k_2$ is determined from	$k_2$ : The submersion factor $k_2$ is determined from	
the following equation.	the following equation.	
$0.8 - f \qquad : f < 0$	0.8 - f : f < 0	
$k_2 = 0.8 - 0.4f \qquad : 0 \le f \le 1$	$k_2 = 0.8 - 0.4f$ : $0 \le f \le 1$ $0.6 - 0.2f$ : $1 < f \le 2.5$	
$0.6 - 0.2f : 1 < f \le 2.5$	$0.6 - 0.2f : 1 < f \le 2.5$	
0.1 : f > 2.5	0.1 : f > 2.5	
where	where	
$f = \frac{h_0 - H_{ice}}{D/2} - 1$	$f = \frac{h_0 - H_{ice}}{D/2} - 1$	
$h_0$ : The depth of the propeller centreline	$h_0$ : The depth of the propeller centreline	
at the lower ice waterline (LIWL) of	at the lower ice waterline (LIWL) of	Typographical
the ship $(m)$ . If $h_0$ is not known,	the ship $(m)$ . If $h_0$ is not known,	correction
$h_0 = D/2$ .	$h_0 = 2/D$ .	IID 12(C 1) D 5.2.0
k3: Propulsion machinery type factor, to be taken		UR I3(Corr.1) Para.5.3.9
as follows.		Same as Chapter 8,
Fixed propulsors: $k_3 = 1$		8.5.5-2, Part I of the
Azimuthing propulsors: $k_3 = 1.2$		Rules
EFFECTIVE DATE AND APPLICATION		
1. The effective date of the amendments is 1 January 202	6.	